

**Product Group : Pipe Plug / KB**

Product Code	Size Usage Range		Max. Working Pressure	Deflated Plug Dimensions		Back Pressure
	Min. Diameter	Max. Diameter		Diameter	Total Length	
	(mm)	(mm)	(bar) / (psi)	(mm)	(mm)	(bar) / (psi)
KB2550	25	50	3.0 / 44	22	150	1.0 / 14,5
KB3570	35	70	3.0 / 44	32	175	0.5 / 7.3
KB50100	50	100	1.5 / 22	47	330	0.5 / 7.3
KB50100/2,5	50	100	2.5 / 36	47	330	1.0 / 14,5
KB70150	70	150	1.5 / 22	68	375	0.5 / 7.3
KB70150/2,5	70	150	2.5 / 36	68	375	1.0 / 14,5
KB100200	100	200	1.5 / 22	91	550	0.5 / 7.3
KB100200/2,5	100	200	2.5 / 36	91	550	1.0 / 14,5
KB150300	150	300	1.5 / 22	140	550	0.5 / 7.3
KB150300/2,5	150	300	2.5 / 36	140	550	1.0 / 14,5
KB200400	200	400	1.5 / 22	187	650	0.5 / 7.3
KB200400/2,5	200	400	2.5 / 36	187	650	1.0 / 14,5
KB200500	200	500	1.5 / 22	187	800	0.5 / 7.3
KB200500/2,5	200	500	2.5 / 36	187	800	1.0 / 14,5
KB300600	300	600	1.5 / 22	286	850	0.5 / 7.3
KB300600/2,5	300	600	2.5 / 36	286	850	1.0 / 14,5
KB375750	375	750	1.5 / 22	361	1000	0.5 / 7.3
KB375750/2,5	375	750	2.5 / 36	361	1000	1.0 / 14,5
KB400800	400	800	1.5 / 22	365	1000	0.5 / 7.3
KB400800/2,5	400	800	2.5 / 36	365	1000	1.0 / 14,6
KB5001000	500	1000	1.5 / 22	486	1100	0.5 / 7.4
KB5001000/2,5	500	1000	2.5 / 36	486	1100	1.0 / 14,7
KB5001200	500	1000	1.5 / 22	486	1450	0.5 / 7.5
KB6001200	600	1200	1.5 / 22	586	1300	0.5 / 7.3
KB6001200/2,5	600	1200	2.5 / 36	586	1300	0.8 / 11.6
KB6001600	600	1200	1.0 / 14,5	586	2050	0.3 / 4.4
KB6001600/1,5	600	1200	1.5 / 22	586	2050	0.4 / 5.8
KB8001600	800	1600	1.0 / 14,5	782	1800	0.5 / 7.3
KB8001800	800	1800	1.0 / 14,5	782	2250	0.4 / 5.8
KB8002000	800	2000	1.0 / 14,5	782	2750	0.4 / 5.8
KB8002200	800	2200	1.0 / 14,5	782	3250	0.3 / 4.4
KB12002400	1200	2400	1.0 / 14,5	1172	3050	0.5 / 7.3
KB12002600	1200	2600	1.0 / 14,5	1172	3050	0.4 / 5.8
KB12002800	1200	2800	1.0 / 14,5	1172	4050	0.3 / 4.4